

PRODUCT-DETAILS

232ERS9W

Wall mounted outlets, 2P+E, 32A, 380 ... 415 V



General Information

Extended Product Type	232ERS9W
Product ID	2CMA101237R1000
EAN	7392696012379
Catalog Description	Wall mounted outlets, 2P+E, 32A, 380 ... 415 V
Long Description	Wall mounted outlet, 2P+E, 32A, 380 ... 415 V Clock Position Of Grounding Contact 9 hour Color code Red

Ordering

EAN	7392696012379
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	89 mm
Product Net Height	117 mm
Product Net Weight	0.31 kg

Container Information

Package Level 1 Width	134 mm
Package Level 1 Depth / Length	177 mm
Package Level 1 Height	467 mm
Package Level 1 Gross Weight	1.55 kg
Package Level 1 EAN	7392696020367
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660169X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616295
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	25 mm
Cable Entry Position	Other
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232ERS9W
Mounting Holes	40x63.5, 40x73.5
Mounting Type	Angled
Number of Poles	3
Order Multiple	5 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I_n)	32 A

Rated Voltage (U _r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

