

## PRODUCT-DETAILS

# 432ERS11W

Wall mounted outlets, 3P+N+E, 32A, 250/440 ...  
265/460 V



## General Information

|                       |                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 432ERS11W                                                                                                          |
| Product ID            | 2CMA101256R1000                                                                                                    |
| EAN                   | 7392696012560                                                                                                      |
| Catalog Description   | Wall mounted outlets, 3P+N+E, 32A, 250/440 ... 265/460 V                                                           |
| Long Description      | Wall mounted outlet, 3P+N+E, 32A, 250/440 ... 265/460 V Clock Position Of Grounding Contact 11 hour Color code Red |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696012560       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 5 piece             |

## Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 89 mm   |
| Product Net Height | 120 mm  |
| Product Net Weight | 0.32 kg |

## Container Information

|                       |        |
|-----------------------|--------|
| Package Level 1 Width | 134 mm |
|-----------------------|--------|

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Depth / Length | 177 mm        |
| Package Level 1 Height         | 467 mm        |
| Package Level 1 Gross Weight   | 1.6 kg        |
| Package Level 1 EAN            | 7392696020626 |
| Package Level 1 Units          | box 5 piece   |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660169X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1616295         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                  |
|---------------------------------|----------------------------------|
| Additional Information          | 3P+N+E                           |
| Ambient Temperature             | -25 ... 40 °C                    |
| Cable Cross-Section             | 2.5 ... 6 mm²                    |
| Cable Diameter                  | 25 mm                            |
| Cable Entry Position            | Other                            |
| Color                           | Red                              |
| Connection Type                 | Screw                            |
| Degree of Protection            | IP67                             |
| Frequency (f)                   | 60 Hz                            |
| Function                        | Wall mounted socket              |
| Housing Material                | Plastic (PA)                     |
| Invoice Description             | Ind. P&S#432ERS11W               |
| Mounting Holes                  | 40x63.5, 40x73.5                 |
| Mounting Type                   | Angled                           |
| Number of Poles                 | 5                                |
| Order Multiple                  | 5 piece                          |
| Product Main Type               | ERS                              |
| Product Name                    | Wall mounted socket              |
| Protection Type                 | Watertight                       |
| Rated Current (I <sub>n</sub> ) | 32 A                             |
| Rated Voltage (U <sub>r</sub> ) | 250/440 ... 265/460 V            |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC700014C0016                  |
| Installation Manual             | 2CMC700014C0016                  |
| RAL Number                      | RAL 7012 - Basalt Grey           |

| Classifications |          |
|-----------------|----------|
| eClass          | 27440510 |
| UNSPSC          | 39120000 |

| Technical         |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

| Categories                                                                                             |
|--------------------------------------------------------------------------------------------------------|
| Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets |

