


PRODUCT-DETAILS

416ERU4W

Panel mounted socket outlets, 3P+N+E, 16A,
57/100 ... 75/130 V



General Information

Extended Product Type	416ERU4W
Product ID	2CMA101301R1000
EAN	7392696013017
Catalog Description	Panel mounted socket outlets, 3P+N+E, 16A, 57/100 ... 75/130 V
Long Description	Panel mounted socket outlet, 3P+N+E, 16A, 57/100 ... 75/130 V Clock Position Of Grounding Contact 4 hour Color code Yellow

Ordering

EAN	7392696013017
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	85 mm
Product Net Height	99 mm
Product Net Weight	0.21 kg

Container Information

Package Level 1 Width	74 mm
-----------------------	-------

Package Level 1 Depth / Length	187 mm
Package Level 1 Height	442 mm
Package Level 1 Gross Weight	2.1 kg
Package Level 1 EAN	7392696021630
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660168X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616293
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Diameter	13 ... 17 mm
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416ERU4W
Mounting Holes	75x75
Mounting Type	Unified straight flange
Number of Poles	5
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I _n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	57/100 ... 75/130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

