

PRODUCT-DETAILS

416RU6B

Panel mounted inlets, 3P+N+E, 16A, 200/346 ...
240/415 V



General Information

Extended Product Type	416RU6B
Product ID	2CMA101640R1000
EAN	7392696016407
Catalog Description	Panel mounted inlets, 3P+N+E, 16A, 200/346 ... 240/415 V
Long Description	Panel mounted inlets, 3P+N+E, 16A, 200/346 ... 240/415 V Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN	7392696016407
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	89 mm
Product Net Weight	0.22 kg

Container Information

Package Level 1 Width	158 mm
Package Level 1 Depth / Length	345 mm
Package Level 1 Height	138 mm
Package Level 1 Gross Weight	2.2 kg
Package Level 1 EAN	7392696016445
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	2396 kg
Package Level 2 EAN	7392696066150
Package Level 2 Units	pallet (lift) 1080 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	13 ... 17 mm
Color	Red
Connection Type	Screw
Cover Color	Black
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind.P-S_416RU6B
Mounting Holes	60-61x60-61
Number of Poles	5

Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

