

## PRODUCT-DETAILS

# 2125MVS3WH

## Industrial Switched Interlocked Socket Outlets, 2P+E, 125 A, >50 ... 250 DC V



### General Information

|                       |                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------|
| Extended Product Type | 2125MVS3WH                                                                          |
| Product ID            | 2CMA101717R1000                                                                     |
| EAN                   | 7392696017176                                                                       |
| Catalog Description   | Industrial Switched Interlocked Socket Outlets, 2P+E, 125 A, >50 ... 250 DC V       |
| Long Description      | Industrial Switched Interlocked Socket Outlets, 2P+E, IP67, 125 A, >50 ... 250 DC V |

### Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696017176       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 175 mm          |
| Product Net Height  | 241 mm          |
| Product Net Weight  | 4.2 kg          |
| Mechanical Drawings | 9AKK107991A3934 |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 260 mm        |
| Package Level 1 Depth / Length | 180 mm        |
| Package Level 1 Height         | 490 mm        |
| Package Level 1 Gross Weight   | 4.2 kg        |
| Package Level 1 EAN            | 7392696017176 |
| Package Level 1 Units          | box 1 piece   |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660160X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC700001D0002 |
| SEMKO Certificate              | 1506655         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Additional Information     | 2P+E                                          |
| Ambient Temperature        | -25 ... 40 °C                                 |
| Cable Cross-Section        | 16 ... 70 mm²                                 |
| Cable Diameter             | 24 ... 48 mm                                  |
| Color                      | Grey                                          |
| Degree of Protection       | IP67 / IP69                                   |
| Function                   | Outlet                                        |
| Invoice Description        | Ind. P&S#2125MVS3WH                           |
| Number of Poles            | 3                                             |
| Product Main Type          | CMVS                                          |
| Product Name               | Industrial Switched Interlocked Socket Outlet |
| Protection Type            | Watertight                                    |
| Rated Current ( $I_n$ )    | 125 A                                         |
| Rated Voltage ( $U_r$ )    | >50 ... 250 V DC                              |
| Standards                  | IEC 60309-1, -2, -4                           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets              |
| Instructions and Manuals   | 2CMC000043M0001                               |
| RAL Number                 | RAL 7001 - Silver Grey                        |

## Classifications

|        |          |
|--------|----------|
| UNSPSC | 39120000 |
|--------|----------|

## Technical

|           |             |
|-----------|-------------|
| Wire Size | 3 ... 1 AWG |
|-----------|-------------|

|                   |                  |
|-------------------|------------------|
| Tightening Torque | WireClamp5.6 N·m |
|-------------------|------------------|

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

