

PRODUCT-DETAILS

363ERT5W

Surface socket outlets, 3P+E, 63 A, 600 ... 690V



General Information

Extended Product Type	363ERT5W
Product ID	2CMA101898R1000
EAN	7392696018982
Catalog Description	Surface socket outlets, 3P+E, 63 A, 600 ... 690V
Long Description	Wall mounted socket, 3P+E, IP67, 63 A, 600 ... 690V, Housing in plastic (PBT). Cable entry with knock-outs 2xM20 on top and 2xM25 on bottom. Cable area 1.5...4 mm ²

Ordering

EAN	7392696018982
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	149 mm
Product Net Height	219 mm
Product Net Weight	1.45 kg

Container Information

Package Level 1 Width	225 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	155 mm
Package Level 1 Gross Weight	1.45 kg
Package Level 1 EAN	7392696018982
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Cable Diameter	17 ... 35 mm
Cable Entry Position	2xM32/M40 + 1xM20 knock-out on top, 2xM20+1xM32/M40 knock-out from bottom
Cable Outlets Per Side	2
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#363ERT5W
Mounting Holes	124x129
Mounting Type	Angled
Number of Poles	4
Order Multiple	1 piece
Product Main Type	ERT
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I_n)	63 A

Rated Voltage (U _r)	600 ... 690 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

