

PRODUCT-DETAILS

463EBT9

Surface inlets, 3P+N+E, 63 A, 120/208 ... 144/250 V



General Information

Extended Product Type	463EBT9
Product ID	2CMA101906R1000
EAN	7392696019064
Catalog Description	Surface inlets, 3P+N+E, 63 A, 120/208 ... 144/250 V
Long Description	Surface inlets, 3P+N+E, IP44, 63 A, 120/208 ... 144/250 V

Ordering

EAN	7392696019064
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	149 mm
Product Net Height	200 mm
Product Net Weight	1.4 kg

Container Information

Package Level 1 Width	225 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	155 mm
Package Level 1 Gross Weight	1.4 kg
Package Level 1 EAN	7392696019064
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm²
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463EBT9
Mounting Holes	124x129
Number of Poles	5
Order Multiple	1 piece
Product Main Type	EBT
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	120/208 ... 144/250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets

Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

