



PRODUCT-DETAILS

4125ERA7W LP

Surface socket outlets for looping, 3P+N+E, 125 A, 277/480 ... 288/500 V

General Information

Extended Product Type	4125ERA7W LP
Product ID	2CMA101921R1000
EAN	7392696019217
Catalog Description	Surface socket outlets for looping, 3P+N+E, 125 A, 277/480 ... 288/500 V
Long Description	Surface socket outlets for looping, 3P+N+E, IP67, 125 A, 277/480 ... 288/500 V

Ordering

EAN	7392696019217
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	230 mm
Product Net Height	222 mm
Product Net Weight	4.3 kg

Container Information

Package Level 1 Width	245 mm
Package Level 1 Depth / Length	235 mm
Package Level 1 Height	515 mm
Package Level 1 Gross Weight	4.3 kg
Package Level 1 EAN	7392696019217
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm²
Cable Entry Position	Other
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#4125ERA7W LP
Mounting Holes	71x71
Number of Poles	5
Order Multiple	1 piece
Product Main Type	ERA
Product Name	Wall mounted socket for looping
Protection Type	Watertight
Rated Current (I_n)	125 A
Rated Voltage (U_r)	480 ... 500 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping