

PRODUCT-DETAILS

363MPR6W

Switched interlocked socket-outlet with RCD, 6h, 30mA, 63A, IP67, 3P+E



General Information

Extended Product Type	363MPR6W
Product ID	2CMA101938R1000
EAN	7392696019385
Catalog Description	Switched interlocked socket-outlet with RCD, 6h, 30mA, 63A, IP67, 3P+E
Long Description	Switched Interlocked Socket Outlet with RCD, earthing sleeve position 6h, 30mA, rated current 63A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

Ordering

EAN	7392696019385
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	174 mm
Product Net Height	336 mm
Product Net Weight	1.9 kg

Container Information

Package Level 1 Width	270 mm
Package Level 1 Depth /	490 mm

Length

Package Level 1 Height	210 mm
Package Level 1 Gross Weight	2.030 kg
Package Level 1 EAN	7392696019385
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	84.96 kg
Package Level 2 EAN	7392696066464
Package Level 2 Units	pallet (lift) 32 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm ²
Cable Diameter	17 ... 35 mm
Cable Entry Position	Top
Cable Outlets Per Side	2xØ25
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Switched interlocked socket outlet with RCD
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#363MPR6W
Mounting Holes	290x100
Mounting Type	Vertical
Number of Poles	4
Number of RCDs 30mA	1
Number of RCDs	1
Order Multiple	1 piece
Product Main Type	CMPR
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	RCD
Rated Current (I _n)	63 A
Rated Residual Current	30 mA
Rated Voltage (U _r)	380 ... 415 V
Recommended Screw	PH2

Driver	
Standards	IEC 60309-1, -2, -4
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000041M0002
Installation Manual	2CMC000041M0002
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets with RCD

