

PRODUCT-DETAILS

FCP-S4/400 690V-5h

FCP-S4/400 690V-5h Panel mounted socket



General Information

Extended Product Type	FCP-S4/400 690V-5h
Product ID	2CMA103372R1000
EAN	7392696033725
Catalog Description	FCP-S4/400 690V-5h Panel mounted socket
Long Description	Panel mounted socket outlets, 3P+E, IP67, 400 A, 380 ... 415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connectors also suitable for marine applications. Aluminum housing. Designed for high temperature.

Ordering

EAN	7392696033725
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	275 mm
Product Net Height	230 mm
Product Net Weight	6.8 kg

Container Information

Package Level 1 Width	352 mm
Package Level 1 Depth / Length	352 mm
Package Level 1 Height	232 mm
Package Level 1 Gross Weight	6.8 kg
Package Level 1 EAN	7392696033725
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+E
Ambient Temperature	-40 ... 100 °C
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Aluminum
Invoice Description	Ind. P&S#FCP-S4/400 690V-5h
Mounting Holes	127x127
Number of Poles	4
Order Multiple	1 piece
Product Main Type	FCP
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	400 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	600 ... 690 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

