

PRODUCT-DETAILS

CUMI-S5/250 690V-5h

CUMI-S5/250 690V-5h Connector Unit with Mechanical Interlock



General Information

Extended Product Type	CUMI-S5/250 690V-5h
Product ID	2CMA103477R1000
EAN	7392696034777
Catalog Description	CUMI-S5/250 690V-5h Connector Unit with Mechanical Interlock
Long Description	Connector Unit with Mechanical Interlock, yellow painted steel enclosure, 800X600X300, CUMI-S5/250 690V-5h, 3P+N+E

Ordering

EAN	7392696034777
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	350 mm
Product Net Height	285 mm
Product Net Weight	25.3 kg

Container Information

Package Level 1 Width	747 mm
Package Level 1 Depth /	747 mm

Length

Package Level 1 Height	287 mm
Package Level 1 Gross Weight	25.3 kg
Package Level 1 EAN	7392696034777
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 70 °C
Cable Diameter	20 ... 65 mm
Cable Entry Position	Up
Color	Black
Connection Type	Screw Clamp
Degree of Protection	IP55
Frequency (f)	50 Hz 60 Hz
Function	Connector Unit with Mechanical Interlock
Housing Material	Steel
Invoice Description	Ind. P&S#CUMI-S5/250 690V-5h
Mounting Holes	310x580
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CUMI
Product Name	Connector Unit with Mechanical Interlock
Rated Current (I _n)	250 A
Rated Voltage (U _r)	347/600 ... 400/690 V
Standards	IEC 60309-1, -2
Sub-Function	C-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440508
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

