

PRODUCT-DETAILS

CUBC-S5/250 1000V-1h

CUBC-S5/250 1000V-1h Connector Unit with Block Contactor



General Information

Extended Product Type	CUBC-S5/250 1000V-1h
Product ID	2CMA103518R1000
EAN	7392696035187
Catalog Description	CUBC-S5/250 1000V-1h Connector Unit with Block Contactor
Long Description	Connector Unit with Block Contactor, yellow painted steel enclosure, 800X600X290, CUBC-S5/250 1000V-1h, 3P+N+E

Ordering

EAN	7392696035187
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	350 mm
Product Net Height	258 mm
Product Net Weight	25.3 kg

Container Information

Package Level 1 Width	747 mm
Package Level 1 Depth /	747 mm

Length

Package Level 1 Height	260 mm
Package Level 1 Gross Weight	25.3 kg
Package Level 1 EAN	7392696035187
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 70 °C
Cable Diameter	20 ... 65 mm
Color	Grey
Connection Type	Screw Clamp
Degree of Protection	IP55
Frequency (f)	AC Hz
Function	Connector Unit with Block Contactor
Housing Material	Steel
Invoice Description	Ind. P&S#CUBC-S5/250 1000V-1h
Mounting Holes	310x580
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CUBC
Product Name	Connector Unit with Block Contactor
Rated Current (I_n)	250 A
Rated Voltage (U_r)	1000 V
Standards	IEC 60309-1, -2
Sub-Function	C-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440508
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

