

PRODUCT-DETAILS

CUCB-S5/250 690V-5h

CUCB-S5/250 690V-5h Connector Unit with Circuit Breaker



General Information

Extended Product Type	CUCB-S5/250 690V-5h
Product ID	2CMA103562R1000
EAN	7392696035620
Catalog Description	CUCB-S5/250 690V-5h Connector Unit with Circuit Breaker
Long Description	Connector Unit with Circuit Breaker, yellow painted steel enclosure, 1200X800X379, CUCB-S5/250 690V-5h, 3P+N+E

Ordering

EAN	7392696035620
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	360 mm
Product Net Height	360 mm
Product Net Weight	47.1 kg

Container Information

Package Level 1 Width	883 mm
Package Level 1 Depth /	883 mm

Length

Package Level 1 Height	362 mm
Package Level 1 Gross Weight	47.1 kg
Package Level 1 EAN	7392696035620
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 70 °C
Cable Diameter	20 ... 65 mm
Color	Black
Connection Type	Screw Clamp
Degree of Protection	IP55
Frequency (f)	50 Hz 60 Hz
Function	Connector Unit with Circuit Breaker
Housing Material	Steel
Invoice Description	Ind. P&S#CUCB-S5/250 690V-5h
Mounting Holes	310x580
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CUCB
Product Name	Connector Unit with Circuit Breaker
Protection Type	Mini circuit breaker
Rated Current (I _n)	250 A
Rated Voltage (U _r)	347/600 ... 400/690 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440508
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

