

PRODUCT-DETAILS

ABB330RU4SP

Panel mounted sockets, 2P+E, 4 hour, Yellow, IP44, 30A, 125V, UL/CSA approved and CE compliant, UL/CSA approved and CE compliant



General Information

Extended Product Type	ABB330RU4SP
Product ID	2CMA104576R1000
EAN	7392696045766
Catalog Description	Panel mounted sockets, 2P+E, 4 hour, Yellow, IP44, 30A, 125V, UL/CSA approved and CE compliant, UL/CSA approved and CE compliant
Long Description	IEC Receptacle for 30A and 125V AC 2P3W Clock Position Of Grounding Contact 4 hour Color code Yellow, UL/CSA approved and CE compliant

Ordering

EAN	7392696045766
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	93 mm
Product Net Weight	0.21 kg

Container Information

Package Level 1 Width	182 mm
Package Level 1 Depth / Length	378 mm
Package Level 1 Height	154 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696053570
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696067188
Package Level 2 Units	pallet (lift) 450 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0022
UL Certificate	E163435-19950105
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Color	Yellow
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#ABB330RU4SP
Mounting Holes	60-61x60-61
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Rated Current (I _n)	30 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	100 ... 130 V
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13

Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700041M0005
Installation Manual	2CMC700041M0005
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

