

PRODUCT-DETAILS

ABB430P5WN

ABB430P5WN Industrial Plug



General Information

Extended Product Type	ABB430P5WN
Product ID	2CMA104968R1000
EAN	7392696049689
Catalog Description	ABB430P5WN Industrial Plug
Long Description	IEC Plug for 30A and 600V AC 3P4W, UL/CSA/NSF approved and CE compliant

Ordering

EAN	7392696049689
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	94 mm
Product Net Height	94 mm
Product Net Weight	0.30 kg

Container Information

Package Level 1 Width	95 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	175 mm
Package Level 1 Gross Weight	0.251 kg
Package Level 1 EAN	7392696057493
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CSA Certificate	2CHC660174X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0022
UL Certificate	E109550-19950105
UL Listing Card	73E2
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Other
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB430P5WN
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TP
Product Name	Industrial Plug
Rated Current (I_n)	30 A
Rated Voltage (U_r)	600 ... 690 V
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets

Instructions and Manuals	No document needed
Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39121402

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

