

PRODUCT-DETAILS

ABB460C5WN

ABB460C5WN Industrial connector



General Information

Extended Product Type	ABB460C5WN
Product ID	2CMA105023R1000
EAN	7392696050234
Catalog Description	ABB460C5WN Industrial connector
Long Description	IEC Connector for 60A and 600V AC 3P4W, UL/CSA/NSF approved and CE compliant

Ordering

EAN	7392696050234
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	108 mm
Product Net Height	112 mm
Product Net Weight	0.83 kg
Mechanical Drawings	9AKK107492A4188

Container Information

Package Level 1 Width	158 mm
Package Level 1 Depth / Length	345 mm
Package Level 1 Height	138 mm
Package Level 1 Gross Weight	0.81 kg
Package Level 1 EAN	7392696050234
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0022
UL Certificate	E163435-19950105
UL Listing Card	7F43
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm²
Cable Diameter	17 ... 35 mm
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB460C5WN
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial connector
Rated Current (I_n)	60 A
Rated Voltage (U_r)	600 ... 690 V
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	No document needed

Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39121413

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

