

PRODUCT-DETAILS

232MVS12WH

Ind. P&S#232MVS12WH



General Information

Extended Product Type	232MVS12WH
Product ID	2CMA105110R1000
EAN	7392696051101
Catalog Description	Ind. P&S#232MVS12WH
Long Description	Switched Interlocked Socket Outlet, vertical, earthing sleeve position 12h, rated current 32A, IP67 watertight Heavy duty, 2-poles+earth, frequency 50-60 Hz, color code Grey

Ordering

EAN	7392696051101
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	160 mm
Product Net Height	205 mm
Product Net Weight	1.830 kg
Mechanical Drawings	9AKK107991A3925

Container Information

Package Level 1 Width	215 mm
Package Level 1 Depth / Length	335 mm
Package Level 1 Height	165 mm
Package Level 1 Gross Weight	1.830 kg
Package Level 1 EAN	7392696051101
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
SEMKO Certificate	2CHC660004X0203

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Other
Color	Grey
Connection Type	Screw
Degree of Protection	IP67
Function	Outlet
Invoice Description	Ind. P&S#232MVS12WH
Number of Poles	3
Product Main Type	CMVS
Product Name	Switched Interlocked Socket Outlet
Rated Current (I _N)	for Pluggable Output 32 A
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000029M0001
Installation Manual	2CMC000029M0001
RAL Number	RAL 7001 - Silver Grey

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

