

PRODUCT-DETAILS

ABB430MF2W

Mechanical Interlock Fused Clock Position Of Grounding Contact 2 hour Color code Green, UL/CSA approved and CE compliant



General Information

Extended Product Type	ABB430MF2W
Product ID	2CMA106037R1000
EAN	7392696060370
Catalog Description	Mechanical Interlock Fused Clock Position Of Grounding Contact 2 hour Color code Green, UL/CSA approved and CE compliant
Long Description	Mechanical Interlock Fused Clock Position Of Grounding Contact 2 hour Color code Green, UL/CSA approved and CE compliant

Ordering

EAN	7392696060370
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	160 mm
Product Net Height	103 mm
Product Net Weight	0.720 kg

Container Information

Package Level 1 Width	169 mm
-----------------------	--------

Package Level 1 Depth / Length	339 mm
Package Level 1 Height	219 mm
Package Level 1 Gross Weight	0.800 kg
Package Level 1 EAN	7392696060370
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CSA Certificate	2CHC660172X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0022
UL Certificate	E109667-20021206
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Entry Position	Other
Color	Green
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	>300 ... 500 Hz
Function	Outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB430MF2W
Mounting Holes	378x145, 128x145
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CMF
Product Name	Switched interlocked socket outlet
Rated Current (I _n)	30 A
Rated Frequency (f)	300 ... 500 Hz
Rated Voltage (U _r)	50 ... 500 V
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700041M0006
Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

UNSPSC	39120000
--------	----------

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

