

PRODUCT-DETAILS

232MVS3WH

Switched interlocked socket-outlet, vertical,
Heavy Duty, 3h, 32A, IP67, 2P+E



General Information

Extended Product Type	232MVS3WH
Product ID	2CMA106218R1000
EAN	7392696062183
Catalog Description	Switched interlocked socket-outlet, vertical, Heavy Duty, 3h, 32A, IP67, 2P+E
Long Description	Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 3h, rated current 32A, IP67 watertight, 2-poles+earth, >50-250V DC

Ordering

EAN	7392696062183
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	160 mm
Product Net Height	307 mm
Product Net Weight	1.83 kg
Mechanical Drawings	9AKK107991A3925

Container Information

Package Level 1 Width	215 mm
-----------------------	--------

Package Level 1 Depth / Length	335 mm
Package Level 1 Height	165 mm
Package Level 1 Gross Weight	1.83 kg
Package Level 1 EAN	7392696062183
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	96.86 kg
Package Level 2 EAN	7392696067553
Package Level 2 Units	pallet (lift) 42 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660004X0203

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Diameter	13 ... 21.5 mm
Color	Grey
Degree of Protection	IP67 IP69
Function	Outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#232MVS3WH
Mounting Holes	130x225
Number of Poles	3
Order Multiple	1 piece
Product Main Type	CMVS
Product Name	Industrial Switched Interlocked Socket Outlet
Rated Current (I_N)	for Pluggable Output 32 A
Rated Voltage (U_r)	>50 ... 250 V DC
Recommended Screw Driver	PH2
Instructions and Manuals	2CMC000029M0001
Installation Manual	2CMC000029M0001

Classifications

eClass	27440510
UNSPSC	39120000

Technical	
Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

