

PRODUCT-DETAILS

432RS5W

432RS5W Wall mounted socket



General Information

Extended Product Type	432RS5W
Product ID	2CMA126670R1000
EAN	7392696266703
Catalog Description	432RS5W Wall mounted socket
Long Description	Surface socket-outlet, earthing sleeve position 5h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Black

Ordering

E-Number (Sweden)	99090218
E-Number (Finland)	2420420
EAN	7392696266703
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	99 mm
Product Net Height	178 mm
Product Net Weight	0.48 kg
Mechanical Drawings	9AKK107991A3847

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696266703
Package Level 1 Units	box 5 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	437.6 kg
Package Level 2 EAN	7392696067867
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	25 mm
Cable Entry Position	Cable entry Ø 25mm
Color	Black
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432RS5W
Mounting Holes	60x148,2
Number of Poles	5
Order Multiple	5 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight

Rated Current (I_n)	32 A
Rated Voltage (U_r)	600 ... 690 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp 1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

