

## PRODUCT-DETAILS

# 363MVS7WH

Switched interlocked socket-outlet, vertical,  
Heavy Duty, 7h, 63A, IP67, 3P+E



## General Information

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 363MVS7WH                                                                                                                                |
| Product ID            | 2CMA162837R1000                                                                                                                          |
| EAN                   | 7392696628372                                                                                                                            |
| Catalog Description   | Switched interlocked socket-outlet, vertical, Heavy Duty, 7h, 63A, IP67, 3P+E                                                            |
| Long Description      | Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 7h, rated current 63A, IP67 watertight, 3-poles+earth |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417026             |
| E-Number (Finland)     | 2417026             |
| E-Number (Norway)      | 2417026             |
| EAN                    | 7392696628372       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 175 mm |
| Product Net Height | 241 mm |

|                     |                 |
|---------------------|-----------------|
| Product Net Weight  | 2.5 kg          |
| Mechanical Drawings | 9AKK107991A3930 |

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Width          | 180 mm                 |
| Package Level 1 Depth / Length | 460 mm                 |
| Package Level 1 Height         | 260 mm                 |
| Package Level 1 Gross Weight   | 2.5 kg                 |
| Package Level 1 EAN            | 7392696628372          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 90 kg                  |
| Package Level 2 EAN            | 7392696068376          |
| Package Level 2 Units          | pallet (lift) 28 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660159X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1506655         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Additional Information | 3P+E                                            |
| Ambient Temperature    | -25 ... 40 °C                                   |
| Cable Cross-Section    | 6 ... 25 mm²                                    |
| Cable Diameter         | 17 ... 35 mm                                    |
| Cable Entry Position   | Knock-out on Top and drill marks down           |
| Cable Outlets Per Side | 1xØ40+1xØ50 mm on top and drill marks on bottom |
| Color                  | Black                                           |
| Connection Type        | Screw                                           |
| Degree of Protection   | IP67<br>IP69                                    |

|                                    |                                                          |
|------------------------------------|----------------------------------------------------------|
| Frequency (f)                      | 50 Hz<br>60 Hz                                           |
| Function                           | Switched Interlocked Socket outlet, vertical, Heavy Duty |
| Housing Material                   | Thermoplastic (PBT)                                      |
| Invoice Description                | IND. P&S#363MVS7WH                                       |
| Mounting Holes                     | 378x145, 128x145                                         |
| Mounting Type                      | Vertical                                                 |
| Number of Auxiliary<br>Contacts NO | 1                                                        |
| Number of Poles                    | 4                                                        |
| Order Multiple                     | 1 piece                                                  |
| Product Main Type                  | CMVS                                                     |
| Product Name                       | Industrial Switched Interlocked Socket Outlet            |
| Protection Type                    | Switched Interlocked                                     |
| Rated Current ( $I_n$ )            | 63 A                                                     |
| Rated Voltage ( $U_r$ )            | 480 ... 500 V                                            |
| Recommended Screw<br>Driver        | PH2                                                      |
| Standards                          | IEC 60309-1, -2, -4                                      |
| Suitable For                       | Switched Interlocked Socket Outlets, Vertical            |
| Suitable for Product Class         | IEC Industrial Plugs and Sockets                         |
| Instructions and Manuals           | 2CMC000043M0001                                          |
| Installation Manual                | 2CMC000043M0001                                          |
| RAL Number                         | RAL 7001 - Silver Grey                                   |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

