

## PRODUCT-DETAILS

# 232MVS1WH

Switched interlocked socket-outlet, vertical,  
Heavy Duty, 1h, 32A, IP67, 2P+E



## General Information

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 232MVS1WH                                                                                                                                |
| Product ID            | 2CMA163275R1000                                                                                                                          |
| EAN                   | 7392696632751                                                                                                                            |
| Catalog Description   | Switched interlocked socket-outlet, vertical, Heavy Duty, 1h, 32A, IP67, 2P+E                                                            |
| Long Description      | Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 1h, rated current 32A, IP67 watertight, 2-poles+earth |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417148            |
| E-Number (Finland)     | 2417148             |
| E-Number (Norway)      | 2417148             |
| EAN                    | 7392696632751       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 160 mm          |
| Product Net Height  | 205 mm          |
| Product Net Weight  | 1.83 kg         |
| Mechanical Drawings | 9AKK107991A3925 |

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Width          | 215 mm                 |
| Package Level 1 Depth / Length | 335 mm                 |
| Package Level 1 Height         | 165 mm                 |
| Package Level 1 Gross Weight   | 1.83 kg                |
| Package Level 1 EAN            | 7392696632751          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 96.86 kg               |
| Package Level 2 EAN            | 7392696068567          |
| Package Level 2 Units          | pallet (lift) 42 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660004X0203 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| Additional Information          | 2P+E                                                     |
| Ambient Temperature             | -25 ... 40 °C                                            |
| Cable Cross-Section             | 2.5 ... 10 mm <sup>2</sup>                               |
| Cable Diameter                  | 13 ... 21.5 mm                                           |
| Cable Entry Position            | Knock-out on Top and drill marks down                    |
| Cable Outlets Per Side          | 1xØ25+1xØ32 mm on top and drill marks on bottom          |
| Color                           | Grey                                                     |
| Connection Type                 | Screw                                                    |
| Degree of Protection            | IP67<br>IP69                                             |
| Frequency (f)                   | AC Hz                                                    |
| Function                        | Switched Interlocked Socket outlet, vertical, Heavy Duty |
| Housing Material                | Thermoplastic (PBT)                                      |
| Invoice Description             | IND. P&S#232MVS1WH                                       |
| Mounting Holes                  | 130x225                                                  |
| Mounting Type                   | Vertical                                                 |
| Number of Poles                 | 3                                                        |
| Order Multiple                  | 1 piece                                                  |
| Product Main Type               | CMVS                                                     |
| Product Name                    | Industrial Switched Interlocked Socket Outlet            |
| Protection Type                 | Switched Interlocked                                     |
| Rated Current (I <sub>n</sub> ) | 32 A                                                     |

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Rated Voltage (U <sub>r</sub> ) | Optional voltage V                            |
| Recommended Screw Driver        | PH2                                           |
| Standards                       | IEC 60309-1, -2, -4                           |
| Suitable For                    | Switched Interlocked Socket Outlets, Vertical |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets              |
| Instructions and Manuals        | 2CMC000029M0001                               |
| Installation Manual             | 2CMC000029M0001                               |
| RAL Number                      | RAL 7001 - Silver Grey                        |

**Classifications**

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

**Technical**

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

**Categories**

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

