

PRODUCT-DETAILS

416BU6 B100

Inlet, panel mounting, 6h, 16A, IP44, unified flange, straight, 3P+N+E, 100pcs



General Information

Extended Product Type	416BU6 B100
Product ID	2CMA166360R1000
EAN	7392696663601
Catalog Description	Inlet, panel mounting, 6h, 16A, IP44, unified flange, straight, 3P+N+E, 100pcs
Long Description	Inlet, panel mounting, earthing sleeve position 6h, rated current 16A, IP44 splashproof, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, bulk pack 100 pcs

Ordering

E-Number (Sweden)	19638830
EAN	7392696663601
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	100 piece

Dimensions

Product Net Width	66 mm
Product Net Height	66 mm
Product Net Weight	0.14 kg

Container Information

Package Level 1 Width	381 mm
Package Level 1 Depth / Length	381 mm
Package Level 1 Height	381 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	7392696663618
Package Level 1 Units	box 100 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	16820 kg
Package Level 2 EAN	7392696068918
Package Level 2 Units	pallet (lift) 1200 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660161X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	13 ... 17 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet for panel mounting
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416BU6 "B100"
Mounting Holes	60x66

Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	100 piece
Product Main Type	EBU
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

