

PRODUCT-DETAILS

432P1W

432P1W Industrial Plug



General Information

Extended Product Type	432P1W
Product ID	2CMA166532R1000
EAN	7392696665322
Catalog Description	432P1W Industrial Plug
Long Description	Plug, earthing sleeve position 1h, rated current 32A, IP67 watertight, 3-poles+neutral+earth

Ordering

E-Number (Sweden)	E2416281
E-Number (Finland)	2416281
E-Number (Norway)	2416281
EAN	7392696665322
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	101 mm
Product Net Height	101 mm
Product Net Weight	0.405 kg

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	4.05 kg
Package Level 1 EAN	7392696665339
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	724.7 kg
Package Level 2 EAN	7392696069045
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Cable entry compression gland
Color	Grey
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	AC Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432P1W
Number of Poles	5
Order Multiple	10 piece
Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2

Suitable For	Plugs
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

