

PRODUCT-DETAILS

432C2W

432C2W Industrial Connector



General Information

Extended Product Type	432C2W
Product ID	2CMA166612R1000
EAN	7392696666121
Catalog Description	432C2W Industrial Connector
Long Description	Connector, earthing sleeve position 2h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 300-500 Hz, color code Green

Ordering

E-Number (Sweden)	2416398
E-Number (Finland)	2416398
E-Number (Norway)	2416398
EAN	7392696666121
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	98 mm
Product Net Height	108 mm
Product Net Weight	0.493 kg

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.563 kg
Package Level 1 EAN	7392696666121
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	117.962 kg
Package Level 2 EAN	7392696069441
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614200
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Cable entry compression gland
Color	Green
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	>300 ... 500 Hz
Function	Connector
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432C2W
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	50 ... 500 V
Recommended Screw Driver	PH2

Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

