

PRODUCT-DETAILS

216BAU12W

216BAU12W Panel mounted inlet



General Information

Extended Product Type	216BAU12W
Product ID	2CMA166682R1000
EAN	7392696666824
Catalog Description	216BAU12W Panel mounted inlet
Long Description	Inlet Panel Mounting, unified flange, angled, earthing sleeve position 12h, rated current 16A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Grey

Ordering

E-Number (Sweden)	2417361
E-Number (Finland)	2417361
E-Number (Norway)	2417361
EAN	7392696666824
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	87 mm
Product Net Height	87 mm

Product Net Weight	0.17 kg
--------------------	---------

Container Information

Package Level 1 Width	110 mm
Package Level 1 Depth / Length	110 mm
Package Level 1 Height	110 mm
Package Level 1 Gross Weight	0.21 kg
Package Level 1 EAN	7392696666824
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	108.2 kg
Package Level 2 EAN	7392696069786
Package Level 2 Units	pallet (lift) 420 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660161X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660161X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	6 ... 13 mm
Color	Grey
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	60 Hz
Function	Inlet, panel mounting, unified flange, angled

Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#216BAU12W
Mounting Holes	79,5x79,5
Mounting Type	unified flange, angled
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TBAU
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Frequency (f)	60 ... 60 Hz
Rated Voltage (U_r)	Isol. Transformer V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

