

PRODUCT-DETAILS

463C1W

463C1W Industrial Connector



General Information

Extended Product Type	463C1W
Product ID	2CMA166914R1000
EAN	7392696669146
Catalog Description	463C1W Industrial Connector
Long Description	Connector, earthing sleeve position 1h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, color code Gray

Ordering

E-Number (Sweden)	2416422
E-Number (Finland)	2416422
E-Number (Norway)	2416422
EAN	7392696669146
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	108 mm
Product Net Height	112 mm
Product Net Weight	0.88 kg
Mechanical Drawings	9AKK107492A4188

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	0.88 kg
Package Level 1 EAN	7392696669146
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	78.08 kg
Package Level 2 EAN	7392696070560
Package Level 2 Units	pallet (lift) 66 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614200
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm ²
Cable Diameter	17 ... 35 mm
Cable Entry Position	Anti-kink sleeve
Color	Grey
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	AC Hz
Function	Connector
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463C1W
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I _n)	63 A
Rated Voltage (U _r)	Optional voltage V
Recommended Screw Driver	PH2

Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

