


PRODUCT-DETAILS

4125RU4W

4125RU4W Panel mounted socket



General Information

Extended Product Type	4125RU4W
Product ID	2CMA167141R1000
EAN	7392696671415
Catalog Description	4125RU4W Panel mounted socket
Long Description	Socket-outlet, panel mounting, earthing sleeve position 4h, rated current 125A, IP67 watertight, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow

Ordering

E-Number (Sweden)	2416783
E-Number (Finland)	2416783
E-Number (Norway)	2416783
EAN	7392696671415
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	115 mm
-------------------	--------

Product Net Height	158 mm
Product Net Weight	1.14 kg
Mechanical Drawings	9AKK107991A3871

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	1.2 kg
Package Level 1 EAN	7392696671415
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	228.8 kg
Package Level 2 EAN	7392696071758
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614199
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm²
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet, panel mounting, unified flange, straight
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#4125RU4W
Mounting Holes	71x71
Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I_n)	125 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	57/100 ... 75/130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Tightening Torque	WireClamp5.6 N·m
-------------------	------------------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

