

PRODUCT-DETAILS

232RS9W

232RS9W Wall mounted socket



General Information

Extended Product Type	232RS9W
Product ID	2CMA167173R1000
EAN	7392696671736
Catalog Description	232RS9W Wall mounted socket
Long Description	Surface socket-outlet, earthing sleeve position 9h, rated current 32A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	2416548
E-Number (Finland)	2421837
E-Number (Norway)	2416548
EAN	7392696671736
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	99 mm
Product Net Height	178 mm
Product Net Weight	0.41 kg
Mechanical Drawings	9AKK107991A3819

Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.5 kg
Package Level 1 EAN	7392696671736
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	107 kg
Package Level 2 EAN	7392696072069
Package Level 2 Units	pallet (lift) 174 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	25 mm
Cable Entry Position	Cable entry Ø 25mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#232RS9W
Mounting Holes	60x148,2
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I _N)	32 A
Rated Voltage (U _r)	380 ... 415 V

Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

