

PRODUCT-DETAILS

363BU1

Inlet, panel mounting, 1h, 63A, IP44, unified flange, straight, 3P+E



General Information

Extended Product Type	363BU1
Product ID	2CMA167230R1000
EAN	7392696672306
Catalog Description	Inlet, panel mounting, 1h, 63A, IP44, unified flange, straight, 3P+E
Long Description	Inlet, panel mounting, earthing sleeve position 1h, rated current 63A, IP44 splashproof, unified flange, straight, 3-poles+earth, color code Grey

Ordering

E-Number (Sweden)	2417354
E-Number (Finland)	2417354
E-Number (Norway)	2417354
EAN	7392696672306
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	103 mm
Product Net Height	103 mm
Product Net Weight	0.53 kg

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.58 kg
Package Level 1 EAN	7392696672306
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	223 kg
Package Level 2 EAN	7392696072472
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	AC Hz
Function	Inlet for panel mounting
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#363BU1
Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TBU
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I _N)	63 A
Rated Voltage (U _r)	Optional voltage V
Recommended Screw	PH2

Driver	
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

