

## PRODUCT-DETAILS

# 263BS1W

## 263BS1W Wall mounted inlet



### General Information

|                       |                                                                                                                |
|-----------------------|----------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 263BS1W                                                                                                        |
| Product ID            | 2CMA167344R1000                                                                                                |
| EAN                   | 7392696673440                                                                                                  |
| Catalog Description   | 263BS1W Wall mounted inlet                                                                                     |
| Long Description      | Surface Inlet, earthing sleeve position 1h, rated current 63A, IP67 watertight, 2-poles+earth, color code Grey |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417261             |
| E-Number (Finland)     | 2417261             |
| E-Number (Norway)      | 2417261             |
| EAN                    | 7392696673440       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 118 mm |
| Product Net Height | 140 mm |
| Product Net Weight | 1.2 kg |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 1.2 kg                  |
| Package Level 1 EAN            | 7392696673440           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 170 kg                  |
| Package Level 2 EAN            | 7392696073035           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660163X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1519130         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                          |
|---------------------------------|--------------------------|
| Additional Information          | 2P+E                     |
| Ambient Temperature             | -25 ... 40 °C            |
| Cable Cross-Section             | 6 ... 25 mm <sup>2</sup> |
| Color                           | Grey                     |
| Connection Type                 | Screw                    |
| Degree of Protection            | IP67<br>IP69             |
| Design                          | Surface mounted plug     |
| Frequency (f)                   | AC Hz                    |
| Function                        | Surface inlet            |
| Housing Material                | Thermoplastic (PBT)      |
| Invoice Description             | Ind. P&S#263BS1W         |
| Mounting Holes                  | 176x76                   |
| Number of Poles                 | 3                        |
| Order Multiple                  | 1 piece                  |
| Product Main Type               | TBS                      |
| Product Name                    | Wall mounted inlet       |
| Protection Type                 | Watertight               |
| Rated Current (I <sub>n</sub> ) | 63 A                     |
| Rated Voltage (U <sub>r</sub> ) | Optional voltage V       |
| Recommended Screw               | PH2                      |

|                            |                                  |
|----------------------------|----------------------------------|
| Driver                     |                                  |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Inlets                   |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000040M0001                  |
| Installation Manual        | 2CMC000040M0001                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

**Classifications**

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

**Technical**

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

**Categories**

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Inlets

