

## PRODUCT-DETAILS

# 363RS1

## Surface socket-outlet, 1h, 63A, IP44, 3P+E



### General Information

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 363RS1                                                                                                                  |
| Product ID            | 2CMA167506R1000                                                                                                         |
| EAN                   | 7392696675062                                                                                                           |
| Catalog Description   | Surface socket-outlet, 1h, 63A, IP44, 3P+E                                                                              |
| Long Description      | Surface socket-outlet, earthing sleeve position 1h, rated current 63A, IP44 splashproof, 2-poles+earth, color code Grey |

### Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2416517             |
| E-Number (Finland)     | 2416517             |
| E-Number (Norway)      | 2416517             |
| EAN                    | 7392696675062       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 107 mm          |
| Product Net Height  | 253 mm          |
| Product Net Weight  | 0.99 kg         |
| Mechanical Drawings | 9AKK107680A0707 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 152 mm                  |
| Package Level 1 Depth / Length | 120 mm                  |
| Package Level 1 Height         | 265 mm                  |
| Package Level 1 Gross Weight   | 0.99 kg                 |
| Package Level 1 EAN            | 7392696675062           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 143.75 kg               |
| Package Level 2 EAN            | 7392696073752           |
| Package Level 2 Units          | pallet (lift) 125 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1614199         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| Additional Information          | 3P+E                                                     |
| Ambient Temperature             | -25 ... 40 °C                                            |
| Cable Cross-Section             | 6 ... 25 mm <sup>2</sup>                                 |
| Cable Entry Position            | Cable entry, M32, alternative rear knock-out cable entry |
| Color                           | Grey                                                     |
| Connection Type                 | Screw                                                    |
| Degree of Protection            | IP44                                                     |
| Frequency (f)                   | AC Hz                                                    |
| Function                        | Surface socket outlet                                    |
| Housing Material                | Thermoplastic (PBT)                                      |
| Invoice Description             | Ind. P&S#363RS1                                          |
| Mounting Holes                  | 170x95                                                   |
| Number of Poles                 | 4                                                        |
| Order Multiple                  | 1 piece                                                  |
| Product Main Type               | TRS                                                      |
| Product Name                    | Wall mounted socket                                      |
| Protection Type                 | Splashproof                                              |
| Rated Current (I <sub>n</sub> ) | 63 A                                                     |
| Rated Voltage (U <sub>r</sub> ) | Optional voltage V                                       |
| Recommended Screw Driver        | PH2                                                      |
| Standards                       | IEC 60309-1, -2                                          |

|                            |                                  |
|----------------------------|----------------------------------|
| Suitable For               | Surface Socket Outlets           |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000038M0001                  |
| Installation Manual        | 2CMC000038M0001                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

**Classifications**

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

**Technical**

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

**Categories**

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

