

PRODUCT-DETAILS

263RU1

Socket-outlet, panel mounting, 1h, 63A, IP44, unified flange, straight, 2P+E



General Information

Extended Product Type	263RU1
Product ID	2CMA167514R1000
EAN	7392696675147
Catalog Description	Socket-outlet, panel mounting, 1h, 63A, IP44, unified flange, straight, 2P+E
Long Description	Socket Outlet Panel Mounting, earthing sleeve position 1h, rated current 63A, IP44 splashproof, 2-poles+earth, color code Grey

Ordering

E-Number (Sweden)	2416674
E-Number (Finland)	2416674
E-Number (Norway)	2416674
EAN	7392696675147
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	98 mm
Product Net Height	135 mm
Product Net Weight	0.6 kg
Mechanical Drawings	9AKK107991A3854

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.6 kg
Package Level 1 EAN	7392696675147
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	230 kg
Package Level 2 EAN	7392696073783
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614199
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	AC Hz
Function	Socket outlet for panel mounting
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#263RU1
Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TRU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I _n)	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	Optional voltage V
Recommended Screw Driver	PH2

Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39121406

Technical

Tightening Torque	WireClamp3.5 N·m
-------------------	------------------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

