

PRODUCT-DETAILS

432MPR6

Switched interlocked socket-outlet with RCD, 6h, 30mA, 32A, IP44, 3P+N+E



General Information

Extended Product Type	432MPR6
Product ID	2CMA167795R1000
EAN	7392696677950
Catalog Description	Switched interlocked socket-outlet with RCD, 6h, 30mA, 32A, IP44, 3P+N+E
Long Description	Switched Interlocked Socket Outlet with RCD, earthing sleeve position 6h, 30mA, rated current 32A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	E2416892
E-Number (Finland)	2421462
E-Number (Norway)	2416892
EAN	7392696677950
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	130 mm
Product Net Height	183 mm
Product Net Weight	1.8 kg

Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	1.9 kg
Package Level 1 EAN	7392696677950
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	105.5 kg
Package Level 2 EAN	7392696074728
Package Level 2 Units	pallet (lift) 45 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Top
Cable Outlets Per Side	2xØ25
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Switched interlocked socket outlet with RCD, 30 mA
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432MPR6
Mounting Holes	290x100
Mounting Type	Vertical
Number of Poles	5
Number of RCDs 30mA	1
Number of RCDs	1
Order Multiple	1 piece
Product Main Type	CMPR
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	RCD

Rated Current (I_n)	32 A
Rated Residual Current	30 mA
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, knock-outs 2xØ25mm
Suitable For	Switched Interlocked Socket Outlets with RCD
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000041M0002
Installation Manual	2CMC000041M0002
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets with RCD

