

## PRODUCT-DETAILS

# 363MM5

Switched interlocked socket-outlet, 5h, 63A, IP44, 3P+E



## General Information

|                       |                                                                                                                                                                  |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 363MM5                                                                                                                                                           |
| Product ID            | 2CMA168035R1000                                                                                                                                                  |
| EAN                   | 7392696680356                                                                                                                                                    |
| Catalog Description   | Switched interlocked socket-outlet, 5h, 63A, IP44, 3P+E                                                                                                          |
| Long Description      | Switched Interlocked Socket Outlet, metal, earthing sleeve position 5h, rated current 63A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Black |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417106            |
| E-Number (Finland)     | 2421374             |
| E-Number (Norway)      | 2417106             |
| EAN                    | 7392696680356       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 165 mm |
| Product Net Height | 177 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 2.5 kg |
|--------------------|--------|

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Width          | 170 mm                 |
| Package Level 1 Depth / Length | 300 mm                 |
| Package Level 1 Height         | 185 mm                 |
| Package Level 1 Gross Weight   | 2.67 kg                |
| Package Level 1 EAN            | 7392696680356          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 206.9 kg               |
| Package Level 2 EAN            | 7392696076258          |
| Package Level 2 Units          | pallet (lift) 70 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                           |
|------------------------|-------------------------------------------|
| Additional Information | 3P+E                                      |
| Ambient Temperature    | -25 ... 40 °C                             |
| Cable Cross-Section    | 6 ... 25 mm²                              |
| Cable Entry Position   | Top and bottom                            |
| Cable Outlets Per Side | 4xM40                                     |
| Color                  | Black                                     |
| Connection Type        | Screw                                     |
| Degree of Protection   | IP44                                      |
| Frequency (f)          | 50 Hz<br>60 Hz                            |
| Function               | Switched Interlocked Socket Outlet, metal |
| Housing Material       | Aluminium                                 |
| Invoice Description    | Ind. P&S#363MM5                           |

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Mounting Holes             | 1819944                                       |
| Mounting Type              | Vertical                                      |
| Number of Poles            | 4                                             |
| Order Multiple             | 1 piece                                       |
| Product Main Type          | CMM                                           |
| Product Name               | Industrial Switched Interlocked Socket Outlet |
| Protection Type            | Switched Interlocked                          |
| Rated Current ( $I_n$ )    | 63 A                                          |
| Rated Voltage ( $U_r$ )    | 600 ... 690 V                                 |
| Recommended Screw Driver   | PH2                                           |
| Standards                  | IEC 60309-1, -2, -4                           |
| Sub-Function               | Cable entry, 4xM40                            |
| Suitable For               | Switched Interlocked Socket Outlets in Metal  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets              |
| Instructions and Manuals   | 2CMC000042M0001                               |
| Installation Manual        | 2CMC000042M0001                               |
| RAL Number                 | RAL 7001 - Silver Grey                        |

---

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

