

## PRODUCT-DETAILS

# 2125MM6

Switched interlocked socket-outlet, 6h, 125A, IP44, 2P+E



## General Information

|                       |                                                                                                                                                                  |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 2125MM6                                                                                                                                                          |
| Product ID            | 2CMA168047R1000                                                                                                                                                  |
| EAN                   | 7392696680479                                                                                                                                                    |
| Catalog Description   | Switched interlocked socket-outlet, 6h, 125A, IP44, 2P+E                                                                                                         |
| Long Description      | Switched Interlocked Socket Outlet, metal, earthing sleeve position 6h, rated current 125A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417116            |
| E-Number (Finland)     | 2417116             |
| E-Number (Norway)      | 2417116             |
| EAN                    | 7392696680479       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 230 mm |
| Product Net Height | 221 mm |
| Product Net Weight | 7.7 kg |

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Width          | 235 mm                 |
| Package Level 1 Depth / Length | 515 mm                 |
| Package Level 1 Height         | 245 mm                 |
| Package Level 1 Gross Weight   | 7.7 kg                 |
| Package Level 1 EAN            | 7392696680479          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 181.7 kg               |
| Package Level 2 EAN            | 7392696076357          |
| Package Level 2 Units          | pallet (lift) 21 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Additional Information          | 2P+E                                          |
| Ambient Temperature             | -25 ... 40 °C                                 |
| Cable Cross-Section             | 16 ... 70 mm <sup>2</sup>                     |
| Cable Entry Position            | Top and bottom                                |
| Cable Outlets Per Side          | 4xM50                                         |
| Color                           | Blue                                          |
| Connection Type                 | Screw                                         |
| Degree of Protection            | IP44                                          |
| Frequency (f)                   | 50 Hz<br>60 Hz                                |
| Function                        | Switched Interlocked Socket Outlet, metal     |
| Housing Material                | Aluminium                                     |
| Invoice Description             | Ind. P&S#2125MM6                              |
| Mounting Holes                  | 1819944                                       |
| Mounting Type                   | Vertical                                      |
| Number of Poles                 | 3                                             |
| Order Multiple                  | 1 piece                                       |
| Product Main Type               | CMM                                           |
| Product Name                    | Industrial Switched Interlocked Socket Outlet |
| Protection Type                 | Switched Interlocked                          |
| Rated Current (I <sub>n</sub> ) | 125 A                                         |
| Rated Voltage (U <sub>r</sub> ) | 200 ... 250 V                                 |
| Recommended Screw               | PH2                                           |

|                            |                                              |
|----------------------------|----------------------------------------------|
| Driver                     |                                              |
| Standards                  | IEC 60309-1, -2, -4                          |
| Suitable For               | Switched Interlocked Socket Outlets in Metal |
| Suitable for Product Class | IEC Industrial Plugs and Sockets             |
| Instructions and Manuals   | 2CMC000044M0001                              |
| Installation Manual        | 2CMC000044M0001                              |
| RAL Number                 | RAL 7001 - Silver Grey                       |

**Classifications**

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

**Technical**

|                   |                  |
|-------------------|------------------|
| Wire Size         | 3 ... 1 AWG      |
| Tightening Torque | WireClamp5.6 N·m |

**Categories**

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

