

PRODUCT-DETAILS

263BU9W

263BU9W Panel mounted inlet



General Information

Extended Product Type	263BU9W
Product ID	2CMA168105R1000
EAN	7392696681056
Catalog Description	263BU9W Panel mounted inlet
Long Description	Inlet, panel mounting, earthing sleeve position 9h, rated current 63A, IP67 watertight, unified flange, straight, 2-poles+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	2417406
E-Number (Finland)	2421968
E-Number (Norway)	2417406
EAN	7392696681056
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	114 mm
Product Net Height	114 mm
Product Net Weight	0.5 kg

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.5 kg
Package Level 1 EAN	7392696681056
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	195 kg
Package Level 2 EAN	7392696076104
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet, panel mounting, unified flange, straight
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#263BU9W
Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TBU
Product Name	Panel mounted inlet

Protection Type	Watertight
Rated Current (I _n)	63 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U _r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

