

PRODUCT-DETAILS

363BU5W

363BU5W Panel mounted inlet



General Information

Extended Product Type	363BU5W
Product ID	2CMA168108R1000
EAN	7392696681087
Catalog Description	363BU5W Panel mounted inlet
Long Description	Inlet, panel mounting, earthing sleeve position 5h, rated current 63A, IP67 watertight, unified flange, straight, 3-poles+earth, frequency 50-60 Hz, color code Black

Ordering

E-Number (Sweden)	2417409
E-Number (Finland)	2417409
E-Number (Norway)	2417409
EAN	7392696681087
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	114 mm
Product Net Height	114 mm

Product Net Weight	0.55 kg
--------------------	---------

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.55 kg
Package Level 1 EAN	7392696681087
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	212.5 kg
Package Level 2 EAN	7392696076135
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Color	Black
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet, panel mounting, unified flange, straight
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#363BU5W
Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TBU
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	600 ... 690 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

