

PRODUCT-DETAILS

232RPM6

Socket-outlet with MCB, 6h, 32A, IP44, 2P+E



General Information

Extended Product Type	232RPM6
Product ID	2CMA168156R1000
EAN	7392696681568
Catalog Description	Socket-outlet with MCB, 6h, 32A, IP44, 2P+E
Long Description	Socket-outlet with MCB, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue

Ordering

E-Number (Sweden)	2466245
E-Number (Finland)	2421982
E-Number (Norway)	2466245
EAN	7392696681568
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	120 mm
Product Net Height	149 mm
Product Net Weight	1.2 kg

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	1.3 kg
Package Level 1 EAN	7392696681568
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	182.5 kg
Package Level 2 EAN	7392696076593
Package Level 2 Units	pallet (lift) 125 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Top
Cable Outlets Per Side	2xØ25
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet with MCB
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#232RPM6
Mounting Holes	171x90
Mounting Type	Vertical
Number of Poles	3
Object Classification Code	2CMT005069
Order Multiple	1 piece
Product Main Type	CRPM
Product Name	Industrial Socket Outlet with Protection
Protection Type	MCB

Rated Current (I _n)	32 A
Rated Voltage (U _r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Sub-Function	Cable entry, knock-outs 2xØ25mm
Suitable For	Socket Outlets with MCB
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000039M0001
Installation Manual	2CMC000039M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Socket Outlets with MCB

