

PRODUCT-DETAILS

432RL1

Industrial Socket Outlets for Looping, 3P+N+E, 32 A, Optional voltage V



General Information

Extended Product Type	432RL1
Product ID	2CMA168432R1000
EAN	7392696684323
Catalog Description	Industrial Socket Outlets for Looping, 3P+N+E, 32 A, Optional voltage V
Long Description	Surface socket-outlet, earthing sleeve position 1h, rated current 32A, IP44 splashproof, 3-poles+neutral+earth, frequency AC, color code Grey

Ordering

E-Number (Sweden)	2417482
E-Number (Finland)	2417482
E-Number (Norway)	2417482
EAN	7392696684323
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	120 mm
Product Net Height	149 mm
Product Net Weight	0.700 kg

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	7392696684323
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	107.5 kg
Package Level 2 EAN	7392696077330
Package Level 2 Units	pallet (lift) 125 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Other
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	AC Hz
Function	Outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#432RL1
Mounting Holes	171x90
Number of Poles	5
Order Multiple	1 piece
Product Main Type	ERL
Product Name	Industrial Socket Outlet for Looping
Protection Type	Splashproof
Rated Current (I _N)	32 A
Rated Voltage (U _r)	Optional voltage V
Recommended Screw Driver	PH2

Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000033M0001
Installation Manual	2CMC000033M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping

