

## PRODUCT-DETAILS

# 4125RL6W

Surface socket-outlet for looping, 6h, 125A, IP67, 3P+N+E



## General Information

|                       |                                                                                                                                                                |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 4125RL6W                                                                                                                                                       |
| Product ID            | 2CMA168536R1000                                                                                                                                                |
| EAN                   | 7392696685368                                                                                                                                                  |
| Catalog Description   | Surface socket-outlet for looping, 6h, 125A, IP67, 3P+N+E                                                                                                      |
| Long Description      | Surface socket-outlet for looping, earthing sleeve position 6h, rated current 125A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417540            |
| E-Number (Finland)     | 2421763             |
| E-Number (Norway)      | 2417540             |
| EAN                    | 7392696685368       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 230 mm          |
| Product Net Height  | 510 mm          |
| Product Net Weight  | 4.3 kg          |
| Mechanical Drawings | 9AKK107991A3883 |

## Container Information

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Width          | 235 mm                 |
| Package Level 1 Depth / Length | 515 mm                 |
| Package Level 1 Height         | 245 mm                 |
| Package Level 1 Gross Weight   | 4.3 kg                 |
| Package Level 1 EAN            | 7392696685368          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 110.3 kg               |
| Package Level 2 EAN            | 7392696077620          |
| Package Level 2 Units          | pallet (lift) 21 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Additional Information          | 3P+N+E                               |
| Ambient Temperature             | -25 ... 40 °C                        |
| Cable Cross-Section             | 16 ... 70 mm <sup>2</sup>            |
| Cable Diameter                  | 24 ... 48 mm                         |
| Cable Entry Position            | Cable entry, knock-outs 2xØ50/25mm   |
| Color                           | Red                                  |
| Connection Type                 | Screw                                |
| Degree of Protection            | IP67                                 |
| Frequency (f)                   | 50 Hz<br>60 Hz                       |
| Function                        | Surface socket outlet for looping    |
| Housing Material                | Thermoplastic (PBT)                  |
| Invoice Description             | Ind. P&S#4125RL6W                    |
| Mounting Holes                  | 204,204, 236x204                     |
| Number of Poles                 | 5                                    |
| Order Multiple                  | 1 piece                              |
| Product Main Type               | TRL                                  |
| Product Name                    | Industrial Socket Outlet for Looping |
| Protection Type                 | Watertight                           |
| Rated Current (I <sub>n</sub> ) | 125 A                                |
| Rated Voltage (U <sub>r</sub> ) | 200/346 ... 240/415 V                |
| Recommended Screw Driver        | PH2                                  |

|                            |                                  |
|----------------------------|----------------------------------|
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Socket Outlets for Looping       |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000038M0001                  |
| Installation Manual        | 2CMC000038M0001                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

---

### Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

---

### Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Looping

