
PRODUCT-DETAILS

216RS6 B80

Industrial Socket Outlets for Surface Mounting, 2P+E, 16 A, 200 ... 250 V



General Information

Extended Product Type	216RS6 B80
Product ID	2CMA192622R1000
EAN	7392696926225
Catalog Description	Industrial Socket Outlets for Surface Mounting, 2P+E, 16 A, 200 ... 250 V
Long Description	Industrial Socket Outlets for Surface Mounting, 2P+E, IP44, 16 A, 200 ... 250 V

Ordering

E-Number (Sweden)	19609020
EAN	7392696926225
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	80 piece

Dimensions

Product Net Width	66 mm
Product Net Height	91 mm
Product Net Weight	0.22 kg
Mechanical Drawings	9AKK107680A0703

Container Information

Package Level 1 Width	66 mm
Package Level 1 Depth / Length	91 mm
Package Level 1 Height	117 mm
Package Level 1 Gross Weight	17.6 kg
Package Level 1 EAN	7392696926232
Package Level 1 Units	box 80 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	16916 kg
Package Level 2 EAN	7392696079013
Package Level 2 Units	pallet (lift) 960 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	18 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216RS6 B80
Mounting Holes	75x54

Number of Poles	3
Order Multiple	80 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

