

PRODUCT-DETAILS

416RS6 B50

Industrial Socket Outlets for Surface Mounting, 3P+N+E, 16 A, 200/346 ... 240/415 V



General Information

Extended Product Type	416RS6 B50
Product ID	2CMA192624R1000
EAN	7392696926249
Catalog Description	Industrial Socket Outlets for Surface Mounting, 3P+N+E, 16 A, 200/346 ... 240/415 V
Long Description	Wall mounted socket, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, Multipack 50 pcs

Ordering

E-Number (Sweden)	19609330
EAN	7392696926249
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	50 piece

Dimensions

Product Net Width	79 mm
Product Net Height	104 mm
Product Net Weight	0.26 kg
Mechanical Drawings	9AKK107680A0705

Container Information

Package Level 1 Width	79 mm
Package Level 1 Depth / Length	104 mm
Package Level 1 Height	134 mm
Package Level 1 Gross Weight	13 kg
Package Level 1 EAN	7392696926256
Package Level 1 Units	box 50 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	7820 kg
Package Level 2 EAN	7392696079051
Package Level 2 Units	pallet (lift) 600 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	18 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416RS6 B50

Mounting Holes	91x67
Number of Poles	5
Order Multiple	50 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

