

PRODUCT-DETAILS

432RS6 B35

Surface socket-outlet, 6h, 32A, IP44, 3P+N+E,
bulk pack 35pcs



General Information

Extended Product Type	432RS6 B35
Product ID	2CMA192630R1000
EAN	7392696926300
Catalog Description	Surface socket-outlet, 6h, 32A, IP44, 3P+N+E, bulk pack 35pcs
Long Description	Surface socket-outlet, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, bulk pack 35pcs

Ordering

E-Number (Sweden)	19610430
E-Number (Finland)	2421216
EAN	7392696926300
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	35 piece

Dimensions

Product Net Width	85 mm
Product Net Height	121 mm
Product Net Weight	0.34 kg
Mechanical Drawings	9AKK107680A0706

Container Information

Package Level 1 Width	179 mm
Package Level 1 Depth / Length	430 mm
Package Level 1 Height	193 mm
Package Level 1 Gross Weight	11.9 kg
Package Level 1 EAN	7392696926317
Package Level 1 Units	box 35 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	5018 kg
Package Level 2 EAN	7392696078900
Package Level 2 Units	pallet (lift) 420 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	22 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry.
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432RS6 "B35"
Mounting Holes	111x72
Number of Poles	5
Order Multiple	35 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I _N)	32 A
Rated Voltage (U _r)	200/346 ... 240/415 V

Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

