

PRODUCT-DETAILS

416R6 B100

Socket-outlet, panel mounting, 6h, 16A, IP44, minimized flange, straight, 3P+N+E, 100pcs



General Information

Extended Product Type	416R6 B100
Product ID	2CMA192636R1000
EAN	7392696926362
Catalog Description	Socket-outlet, panel mounting, 6h, 16A, IP44, minimized flange, straight, 3P+N+E, 100pcs
Long Description	Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	19614430
EAN	7392696926362
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	100 piece

Dimensions

Product Net Width	66 mm
Product Net Height	89 mm
Product Net Weight	0.17 kg

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	17 kg
Package Level 1 EAN	7392696926379
Package Level 1 Units	box 100 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	226 kg
Package Level 2 EAN	7392696078931
Package Level 2 Units	pallet (lift) 1200 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	13 ... 17 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet for panel mounting
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416R6 "B100"
Mounting Holes	51x51

Mounting Type	minimized flange, straight
Number of Poles	5
Order Multiple	100 piece
Product Main Type	ER
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

