

PRODUCT-DETAILS

216RU6 B100

Industrial socket outlets for panel mounting,
2P+E, 16 A, 200 ... 250 V



General Information

Extended Product Type	216RU6 B100
Product ID	2CMA192640R1000
EAN	7392696926409
Catalog Description	Industrial socket outlets for panel mounting, 2P+E, 16 A, 200 ... 250 V
Long Description	Industrial socket outlets for panel mounting, 2P+E, IP44, 16 A, 200 ... 250 V

Ordering

E-Number (Sweden)	19614520
EAN	7392696926409
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	100 piece

Dimensions

Product Net Width	75 mm
Product Net Height	79 mm
Product Net Weight	0.15 kg

Container Information

Package Level 1 Width	75 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	85 mm
Package Level 1 Gross Weight	15 kg
Package Level 1 EAN	7392696926416
Package Level 1 Units	box 100 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	18020 kg
Package Level 2 EAN	7392696078894
Package Level 2 Units	pallet (lift) 1200 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	6 ... 13 mm
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216RU6 B100
Mounting Holes	60-61x60-61
Number of Poles	3
Order Multiple	100 piece

Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

