

PRODUCT-DETAILS

432RU6 B60

Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+N+E, 60pcs



General Information

Extended Product Type	432RU6 B60
Product ID	2CMA192658R1000
EAN	7392696926584
Catalog Description	Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+N+E, 60pcs
Long Description	Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	19616330
EAN	7392696926584
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	60 piece

Dimensions

Product Net Width	75 mm
Product Net Height	102 mm
Product Net Weight	0.24 kg

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	14.4 kg
Package Level 1 EAN	7392696926591
Package Level 1 Units	box 60 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	10388 kg
Package Level 2 EAN	7392696078955
Package Level 2 Units	pallet (lift) 720 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet for panel mounting
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432RU6 "B60"
Mounting Holes	60-61x60-61
Mounting Type	unified flange, straight
Number of Poles	5

Order Multiple	60 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

