

PRODUCT-DETAILS

463RU6 B25

463RU6 B25 Panel mounted socket



General Information

Extended Product Type	463RU6 B25
Product ID	2CMA192664R1000
EAN	7392696926645
Catalog Description	463RU6 B25 Panel mounted socket
Long Description	Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	19617210
EAN	7392696926645
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	25 piece

Dimensions

Product Net Width	104 mm
Product Net Height	135 mm
Product Net Weight	0.72 kg
Mechanical Drawings	9AKK107991A3864

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	18 kg
Package Level 1 EAN	7392696926652
Package Level 1 Units	box 25 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	5420 kg
Package Level 2 EAN	7392696078993
Package Level 2 Units	pallet (lift) 300 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614199
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet for panel mounting
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463RU6 "B25"
Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	5

Order Multiple	25 piece
Product Main Type	TRU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Tightening Torque	WireClamp3.5 N·m
-------------------	------------------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

