

PRODUCT-DETAILS

432BU6 B75

Inlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+N+E, 75pcs



General Information

Extended Product Type	432BU6 B75
Product ID	2CMA192666R1000
EAN	7392696926669
Catalog Description	Inlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+N+E, 75pcs
Long Description	Inlet, panel mounting, earthing sleeve position 6h, rated current 32A, IP44 splashproof, unified flange, straight, 2-poles+earth, frequency 50-60 Hz, color code Red, bulk pack 75 pcs

Ordering

E-Number (Sweden)	19640330
EAN	7392696926669
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	75 piece

Dimensions

Product Net Width	76 mm
Product Net Height	79 mm
Product Net Weight	0.2 kg

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	15 kg
Package Level 1 EAN	7392696926676
Package Level 1 Units	box 75 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	13520 kg
Package Level 2 EAN	7392696078863
Package Level 2 Units	pallet (lift) 900 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660162X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet for panel mounting
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432BU6 "B75"
Mounting Holes	60x66
Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	75 piece
Product Main Type	EBU
Product Name	Panel mounted inlet
Protection Type	Splashproof

Rated Current (I_n)	32 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

