

PRODUCT-DETAILS

463BU6 B25

463BU6 B25 Panel mounted inlet



General Information

Extended Product Type	463BU6 B25
Product ID	2CMA192668R1000
EAN	7392696926683
Catalog Description	463BU6 B25 Panel mounted inlet
Long Description	Inlet, panel mounting, earthing sleeve position 6h, rated current 63A, IP44 splashproof, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, bulk pack 25 pcs

Ordering

E-Number (Sweden)	19641210
EAN	7392696926683
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	25 piece

Dimensions

Product Net Width	103 mm
Product Net Height	103 mm
Product Net Weight	0.62 kg

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	15.5 kg
Package Level 1 EAN	7392696926690
Package Level 1 Units	box 25 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	4670 kg
Package Level 2 EAN	7392696079037
Package Level 2 Units	pallet (lift) 300 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Color	Red
Connection Type	Screw
Cover Color	Black
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet for panel mounting
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463BU6 "B25"

Mounting Holes	61x61
Mounting Type	unified flange, straight
Number of Poles	5
Order Multiple	25 piece
Product Main Type	TBU
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	63 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Inlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

